



Illustrative picture

**SPECIFICS**

<b>Description</b>	Product type	Movable plug low voltage 50/60 Hz IP67
	Article code	8413
	Commercial Series	SERIES 10 IEC 309 IP67

<b>General Data</b>	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6	Cable clamp tightening capacity	mm 11,5 - 20
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 15,8x9,8x9,8	Weight	kg 0,233

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

<b>Standards</b>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<b>Features package</b>	<b>Descriptions</b>		<b>N/pieces</b>	<b>Weight/kg</b>
	Article		1	0,233
	Package innerbox		4	1,022
	Packaging		60	15,95

<b>Dimensions</b>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>140</td> <td>140</td> <td>140</td> <td>161</td> <td>161</td> <td>161</td> </tr> <tr> <td>B</td> <td>71</td> <td>77</td> <td>87</td> <td>92</td> <td>92</td> <td>98</td> </tr> <tr> <td>C</td> <td>46.5</td> <td>53.5</td> <td>60.5</td> <td>62.5</td> <td>62.5</td> <td>69.5</td> </tr> <tr> <td>D</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table>							Amp Poles	16A			32A			3	4	5	3	4	5	A	140	140	140	161	161	161	B	71	77	87	92	92	98	C	46.5	53.5	60.5	62.5	62.5	69.5	D	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22
		Amp Poles	16A			32A																																											
3	4		5	3	4	5																																											
A	140	140	140	161	161	161																																											
B	71	77	87	92	92	98																																											
C	46.5	53.5	60.5	62.5	62.5	69.5																																											
D	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22																																											



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057