



Illustrative picture

SPECIFICS

| | | |
|--------------------|-------------------|--|
| Description | Product type | Movable plug low voltage 50/60 Hz IP67 |
| | Article code | 8213 |
| | Commercial Series | SERIES 10 IEC 309 IP67 |

| | | | | |
|---------------------|------------------------|-----------------|---------------------------------|----------------|
| General Data | Poles | N° 2P+E | Type of material | Halogen free |
| | Current | A 16 | Type of terminal | Screw PH2 |
| | Voltage | V~ 200-250 | Terminal inlet diameter | mm 3,7 |
| | Earth contact position | h 6 | Cable clamp tightening capacity | mm 6,5 - 15 |
| | Degree of protection | IP 67 | Dimensional stability | °C -25 /+70 |
| | Impact Resistance | IK 8 | Resistance glow wire test | °C +650 / +850 |
| | Insulation Resistance | MΩ >10 | Working temperature | °C -25 + 55 |
| | Dimensions LxDxH | cm 12,5x8,7x8,7 | Weight | kg 0,13 |

| Behaviour with chemical and atmospheric agents | | | | | | | | | | | |
|--|-------------------|-----------|--------------|-----------|-------------------|-------------------|-----------|-----------|-------------|-----------|--|
| Saline Solution | Acids | | Bases | | Solvents | | | | Mineral Oil | UV rays | |
| | Concentrated | Diluted | Concentrated | Diluted | Hexane | Benzol | Acetone | Alcohol | | | |
| Resistant | Limited Resistant | Resistant | Resistant | Resistant | Limited Resistant | Limited Resistant | Resistant | Resistant | Resistant | Resistant | |

| | | | |
|------------------|----------------|----------------|------------|
| Standards | CEI EN 60309-1 | CEI EN 60309-2 | 2014/35/UE |
|------------------|----------------|----------------|------------|

| | | | | |
|-------------------------|---------------------|--|-----------------|------------------|
| Features package | Descriptions | | N/pieces | Weight/kg |
| | Article | | 1 | 0,13 |
| | Package innerbox | | 10 | 1,39 |
| | Packaging | | 150 | 21,47 |

| Dimensions | | <table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>140</td> <td>140</td> <td>140</td> <td>161</td> <td>161</td> <td>161</td> </tr> <tr> <td>B</td> <td>71</td> <td>77</td> <td>87</td> <td>92</td> <td>92</td> <td>98</td> </tr> <tr> <td>C</td> <td>46.5</td> <td>53.5</td> <td>60.5</td> <td>62.5</td> <td>62.5</td> <td>69.5</td> </tr> <tr> <td>D</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table> | Amp Poles | 16A | | | 32A | | | 3 | 4 | 5 | 3 | 4 | 5 | A | 140 | 140 | 140 | 161 | 161 | 161 | B | 71 | 77 | 87 | 92 | 92 | 98 | C | 46.5 | 53.5 | 60.5 | 62.5 | 62.5 | 69.5 | D | 6-15 | 6-15 | 8-16 | 11.5-20 | 11.5-20 | 11.5-22 |
|-------------------|------|---|-----------|---------|---------|---------|-----|--|--|---|---|---|---|---|---|---|-----|-----|-----|-----|-----|-----|---|----|----|----|----|----|----|---|------|------|------|------|------|------|---|------|------|------|---------|---------|---------|
| | | Amp Poles | | 16A | | | 32A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | 4 | | 5 | 3 | 4 | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 140 | 140 | 140 | 161 | 161 | 161 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | 71 | 77 | 87 | 92 | 92 | 98 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 46.5 | 53.5 | 60.5 | 62.5 | 62.5 | 69.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | 6-15 | 6-15 | 8-16 | 11.5-20 | 11.5-20 | 11.5-22 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| Rev | Date | Technical Manager |
|-----|--------|-------------------|
| 01 | 7/1/20 | Romano Rosi |

CERTIFICATO N° 9105.RO53 - UNI EN ISO 9001:2015

Reg. A.E.E.n° IT17100000010057