













Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	Anti-crushing plug in rubber 16A 2P+E 250V S11
	Article code	<b>RS78006</b>
	Commercial Series	ANTI-CRUSHING SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	/					
	Current	A 16	Dimensional stability	°C -25 /+70					
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750					
	Degree of protection	IP 20	Working temperature	°C , -15 + 35					
	Impact Resistance	IK 8	Weight	kg 0,034					
	Insulation Resistance	MΩ >10							
	Dimensions LxDxH	cm 9,3x4,3x1,8							
	Behaviour with chemical and atmospheric agents								
	Acids		Bases		Solvents			Mineral Oil	UV rays
Saline Solution	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI 23-50	2011/65/UE
------------------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,034
	Package innerbox		25	0,94
	Packaging		300	11,9



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	<i>Romano Rosi</i>