



Illustrative picture

SPECIFICS

Description	Product type	Movable socket low voltage 50/60 Hz IP67
	Article code	8225
	Commercial Series	SERIES 11 IEC 309 IP67

General Data	Poles	N° 3P+N+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 200/346-240/415	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6	Cable clamp tightening capacity	mm 6,5 - 15
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 14,8x8,6x8,6	Weight	kg 0,265

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,265
	Package innerbox		4	1,15
	Packaging		60	17,87

Dimensions			<table border="1"> <thead> <tr> <th>Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th></th> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>153</td> <td>152</td> <td>154</td> <td>168</td> <td>168</td> <td>168</td> </tr> <tr> <td>B</td> <td>79</td> <td>85</td> <td>95</td> <td>97</td> <td>99</td> <td>106</td> </tr> <tr> <td>C</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table>						Amp Poles	16A			32A				3	4	5	3	4	5	A	153	152	154	168	168	168	B	79	85	95	97	99	106	C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22
	Amp Poles	16A			32A																																						
	3	4	5	3	4	5																																					
A	153	152	154	168	168	168																																					
B	79	85	95	97	99	106																																					
C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22																																					



CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi