

Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Movable socket low voltage 50/60 Hz IP67
	Article code	8524
	Commercial Series	SERIES 11 IEC 309 IP67

<i>General Data</i>	Poles	N° 3P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 380-415	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6	Cable clamp tightening capacity	mm 11,5 - 20
	Degree of protection	IP 67	Dimensional stability	°C -25 / +70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 16,8x10,2x10,2	Weight	kg 0,307

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,307
	Package innerbox		4	1,318
	Packaging		60	20,39

<i>Dimensions</i>			<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>153</td> <td>152</td> <td>154</td> <td>168</td> <td>168</td> <td>168</td> </tr> <tr> <td>B</td> <td>79</td> <td>85</td> <td>95</td> <td>97</td> <td>99</td> <td>106</td> </tr> <tr> <td>C</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11,5-20</td> <td>11,5-20</td> <td>11,5-22</td> </tr> </tbody> </table>						Amp Poles	16A			32A			3	4	5	3	4	5	A	153	152	154	168	168	168	B	79	85	95	97	99	106	C	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
	Amp Poles	16A			32A																																					
3		4	5	3	4	5																																				
A	153	152	154	168	168	168																																				
B	79	85	95	97	99	106																																				
C	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22																																				