



Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	Movable socket low voltage 50/60 Hz IP44
	Article code	9525
	Commercial Series	SERIES 11 IEC 309 IP44

<i>General Data</i>	Poles	N° 3P+N+E	Type of material	Halogen free																														
	Current	A 32	Type of terminal	Screw PH2																														
	Voltage	V~ 200/346-240/415	Terminal inlet diameter	mm 4,6																														
	Earth contact position	h 6	Cable clamp tightening capacity	mm 11,5 - 20																														
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70																														
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850																														
	Insulation Resistance	MΩ >10	Working temperature	°C , -25 + 55																														
	Dimensions LxDxH	cm 16,5x9,8x9,8	Weight	kg 0,303																														
	Behaviour with chemical and atmospheric agents																																	
	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Saline Solution</th> <th colspan="2">Acids</th> <th colspan="2">Bases</th> <th colspan="4">Solvents</th> <th rowspan="2">Mineral Oil</th> <th rowspan="2">UV rays</th> </tr> <tr> <th>Concentrated</th> <th>Diluted</th> <th>Concentrated</th> <th>Diluted</th> <th>Hexane</th> <th>Benzol</th> <th>Acetone</th> <th>Alcohol</th> </tr> </thead> <tbody> <tr> <td>Resistant ●</td> <td>Limited Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Limited Resistant ●</td> <td>Limited Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> </tr> </tbody> </table>					Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Limited Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays																								
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol																										
Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Limited Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Resistant ●																								

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,303
	Package innerbox		3	0,999
	Packaging		45	15,605

<i>Dimensions</i>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>150</td> <td>150</td> <td>152</td> <td>163</td> <td>163</td> <td>166</td> </tr> <tr> <td>B</td> <td>81</td> <td>87</td> <td>96</td> <td>99</td> <td>99</td> <td>106</td> </tr> <tr> <td>C</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table>	Amp Poles	16A			32A			3	4	5	3	4	5	A	150	150	152	163	163	166	B	81	87	96	99	99	106	C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22
	Amp Poles	16A			32A																															
3		4	5	3	4	5																														
A	150	150	152	163	163	166																														
B	81	87	96	99	99	106																														
C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22																														



Rev	Date	Technical Manager
01	7/1/20	Romano Pisci

CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057