



Illustrative picture

**SPECIFICS**

Description	Product type	Movable socket low voltage 50/60 Hz IP44
	Article code	9524
	Commercial Series	SERIES 11 IEC 309 IP44

General Data	Poles	N° 3P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 380-415	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6	Cable clamp tightening capacity	mm 11,5 - 20
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C , -25 + 55
	Dimensions LxDxH	cm 16,5x9,8x9,8	Weight	kg 0,273

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
-----------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,273
	Package innerbox		4	1,182
	Packaging		60	18,35

Dimensions		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>150</td> <td>150</td> <td>152</td> <td>163</td> <td>163</td> <td>166</td> </tr> <tr> <td>B</td> <td>81</td> <td>87</td> <td>96</td> <td>99</td> <td>99</td> <td>106</td> </tr> <tr> <td>C</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table>	Amp Poles	16A			32A			3	4	5	3	4	5	A	150	150	152	163	163	166	B	81	87	96	99	99	106	C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22
		Amp Poles		16A			32A																													
3	4		5	3	4	5																														
A	150	150	152	163	163	166																														
B	81	87	96	99	99	106																														
C	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22																														



Rev	Date	Technical Manager
01	7/1/20	Romano Pisci

CERTIFICATO N° 9105.ROSS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057