



Illustrative picture

SPECIFICS

Description	Product type	Movable plug low voltage 50/60 Hz IP44
	Article code	9413
	Commercial Series	SERIES 10 IEC 309 IP44

General Data	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 32	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 4,6
	Earth contact position	h 6	Cable clamp tightening capacity	mm 11,5 - 20
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 15,2x7x7	Weight	kg 0,2

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,2
	Package innerbox		5	1,09
	Packaging		75	16,97

Dimensions		<table border="1"> <thead> <tr> <th rowspan="2">Amp</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>Poles</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>A</td> <td>140</td> <td>140</td> <td>140</td> <td>161</td> <td>161</td> <td>161</td> </tr> <tr> <td>B</td> <td>106</td> <td>106</td> <td>106</td> <td>122.5</td> <td>122.5</td> <td>122.5</td> </tr> <tr> <td>C</td> <td>46.5</td> <td>53.5</td> <td>60.5</td> <td>62.5</td> <td>62.5</td> <td>69.5</td> </tr> <tr> <td>D</td> <td>56</td> <td>60.5</td> <td>68</td> <td>72</td> <td>72</td> <td>69</td> </tr> <tr> <td>E</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11.5-20</td> <td>11.5-20</td> <td>11.5-22</td> </tr> </tbody> </table>						Amp	16A			32A			3	4	5	3	4	5	Poles							A	140	140	140	161	161	161	B	106	106	106	122.5	122.5	122.5	C	46.5	53.5	60.5	62.5	62.5	69.5	D	56	60.5	68	72	72	69	E	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22
		Amp	16A			32A																																																								
			3	4	5	3	4	5																																																						
		Poles																																																												
		A	140	140	140	161	161	161																																																						
		B	106	106	106	122.5	122.5	122.5																																																						
		C	46.5	53.5	60.5	62.5	62.5	69.5																																																						
D	56	60.5	68	72	72	69																																																								
E	6-15	6-15	8-16	11.5-20	11.5-20	11.5-22																																																								



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT1710000010057